

# OBJECT CARPET

## Typical characteristics

Name of article  
Method of production ISO 2424  
Width ISO 3018  
Surface structure ISO 2424  
Colourways  
Pile material ISO 2424  
Primary backing ISO 2424  
Secondary backing ISO 2424  
Overall weight ISO 8543  
Overall thickness ISO 1765  
Pile service weight



## Struttura

Tufted  
approx. 400  
Loop  
Style  
100% Econyl by Aquafil  
PES  
Conductive action back  
approx. 2000 g/m<sup>2</sup>  
approx. 7,0 - 8,0 mm  
approx. 800 g/m<sup>2</sup>

## Application

Wearability EN 1307 commercial use heavy (33)  
Comfort class EN 1307 LC2

## Ecological characteristics

Conformity certificate 1658-CPR-3032  
DOP 1045-126868  
EPD (Environmental Product Declaration) EPD-GUT-20160117-CCA1-EN

## Fastness

Light fastness ISO 105-B02 ≥ 6  
Water fastness EN ISO 105 E01 ≥ 5  
Friction fastness EN ISO 105-X12 ≥ 5



Release Date 21.12.2022.

OBJECT CARPET GmbH Marie-Curie-Strasse 3 D-73770 Denkendorf  
Fon +49 (0) 711 / 34 02-0 Fax +49 (0) 711 / 34 02-122 technicalsupport@object-carpet.com